



# SINGAPORE GREEN BUILDING PRODUCT CERTIFICATE

AWARDED TO

**Wefatherm GmbH**

Adolf-Oesterheld-Strasse 28, Wunstorf, Germany  
Germany D-31515

FOR THE PRODUCT

**Pipe & Fittings - Potable Water**

PRODUCT BRAND

**Wefatherm**

PRODUCT MODEL

[Pipes] SDR 11 (Standard-PP-R) Ø20, Ø25, Ø32, Ø40, Ø50, Ø63, Ø75, Ø90, Ø110, Ø125 || SDR 6 (Standard-PP-R) Ø20, Ø25, Ø32, Ø40, Ø50, Ø63, Ø75, Ø90, Ø110, Ø125, [Fittings] Bridge m/m (Standard-PP-R) Ø20, Ø25 || Socket (Standard-PP-R) Ø20, Ø25, Ø32, Ø40, Ø50, Ø63, Ø75, Ø90 || Reducer (Standard-PP-R) Ø25/20, Ø32/20, Ø32/25, Ø40/20, Ø40/25, Ø40/32, Ø50/20, Ø50/25, Ø50/32, Ø50/40, Ø63/25, Ø63/32, Ø63/40, Ø63/50, Ø75/50, Ø75/63 || Tee 90° (Standard-PP-R) Ø20, Ø25, Ø32, Ø40, Ø50, Ø63 || Tee reduced 90° (Standard-PP-R) Ø25x20x25, Ø32x20x32, Ø32x25x32, Ø40x20x40, Ø40x25x40, Ø40x32x40, Ø50x20x50, Ø50x25x50, Ø50x32x50, Ø50x40x50, Ø63x25x63, Ø63x32x63, Ø63x40x63, Ø63x50x63 || Elbow 90° (Standard-PP-R) Ø20, Ø25, Ø32, Ø40, Ø50, Ø63, Ø75, Ø90 || Elbow 45° (Standard-PP-R) Ø20, Ø25, Ø32 || End cap (Standard-PP-R) Ø20, Ø25, Ø32, Ø40, Ø50, Ø63, Ø75, Ø90 || Transition round female (Standard-PP-R) Ø20x1/2", Ø20x3/4", Ø25x1/2", Ø25x3/4" || Transition hexagon female (Standard-PP-R) Ø32x1", Ø40x1 1/4", Ø50x1 1/2", Ø63x2", Ø75x 2" || Transition hexagon male (Standard-PP-R) Ø32x1", Ø40x1 1/4", Ø50x1 1/2", Ø63x2", Ø75x 2 1/2", Ø90x3", Ø110x3", Ø110x4" || Transition elbow 90° female (Standard-PP-R) Ø20x1/2", Ø20x3/4", Ø25x1/2", Ø25x3/4", Ø32x3/4", Ø32x1" || Transition elbow 90° male (Standard-PP-R) Ø20x1/2", Ø20x3/4", Ø25x1/2", Ø25x3/4", Ø32x3/4", Ø32x1" || Transition tee female (Standard-PP-R) Ø20x1/2"x20, Ø20x3/4"x20, Ø25x1/2"x25, Ø25x3/4"x25, Ø32x3/4"x32, Ø32x1"x32 || Back plate elbow female (Standard – PP-R) Ø20x1/2", Ø20x3/4", Ø25x1/2", Ø25x3/4" || Weld-in saddle (Standard – PP-R) Ø40/20, Ø40/25, Ø50/20, Ø50/25, Ø63/20, Ø63/25, Ø75/20, Ø75/25, Ø90/20, Ø90/25, Ø110/20, Ø110/25,



Ø125/20, Ø125/25 || Weld-in saddle female (Standard – PP-R)  
Ø40x1/2", Ø50x1/2", Ø63x1/2", Ø75x1/2", Ø90x1/2", Ø110x1/2",  
Ø125x1/2" // Ø40x3/4", Ø50x3/4", Ø63x3/4", Ø75x3/4", Ø90x3/4",  
Ø110x3/4", Ø125x3/4" || Weld-in saddle male (Standard – PP-R)  
Ø40x1/2", Ø50x1/2", Ø63x1/2", Ø75x1/2", Ø90x1/2", Ø110x1/2",  
Ø125x1/2" // Ø40x3/4", Ø50x3/4", Ø63x3/4", Ø75x3/4", Ø90x3/4",  
Ø110x3/4", Ø125x3/4"

THE PRODUCT HAS BEEN ASSESSED ACCORDING  
TO THE ASSESSMENT CRITERIA OF SINGAPORE  
GREEN BUILDING PRODUCT CERTIFICATION SCHEME.  
IT HAS BEEN AWARDED THE RATING:

Director  
SGBC Pte Ltd



Certificate Number	Original Issue Date	Revised Date	Valid Till
SGBP 4710	09 May 2022	-	08 May 2024

✓Good    ✓✓Very Good    ✓✓✓Excellent    ✓✓✓✓Leader

The use and reliance on this certificate is subject to the terms and conditions of the Singapore Green Building Product Certification Scheme. Revised certificates may also be issued at the discretion of the Council. The certification status may be verified at the Singapore Green Building Council website ([www.sgbc.sg](http://www.sgbc.sg)).

